

Leading the Way in Road Safety

Night and day visibility testing of road markings and road traffic signs.

Road Signs Visibility

Sign Retroreflection

Road Marking Visibility

Marking Thickness

Skid Resistance

Marking Retroreflection





Content

Our Portfolio	3
Zehntner ZRM	5
Zehntner ZDR 6020 RL	11
Zehntner ZRS 6060	13
Zehntner ZMM 5000	19
Zehntner Mapping Tools	21

Our Portfolio

Marking Retroreflection

All types of road and airport markings. Day and night visibility. Wet and dry conditions.



ZRM 6006 RL-Qd



ZRM 6010 RL



ZRM 6013+ RL-Qd

Sign Reflection

Visibility measurements of traffic and road signs and reflective materials.



ZRS 6060

Marking Thickness

Dry film thickness measurement.



ZRM 6014 RL-Qd



ZDR 6020 RL



ZMM 5000



Zehntner ZRM 6014

Static Retroreflectometers

The industry standard for day and night visibility measurements of road markings



ZRM 6006 RL-Qd




ZRM 6013+ RL-Qd



ZRM 6010 RL



ZRM 6014 RL-Qd



Versatility

Gather data from night and day visibility effectively, anytime and on any road surface.




Accuracy

Accuracy and ultrafast retroreflection measurements (RL and Qd) in about 2 seconds thanks to intelligent electronics paired with Swiss Made optics.



Productivity

Redefine your measurements with precise geolocation and high-resolution images and create comprehensive reports quickly and with ease.



Note: ZRM 6014 advanced shown on this page. ZRM 6014 is available in three models basic, pro & advanced depending on the chosen features.

Model Overview

ZRM is available in two models (Pro & Advanced) depending on the chosen features depicted in the following Model table:



X: Included
O: Extra Features

ZRM 6006 ZRM 6013+ ZRM 6014 ZRM 6010

	ZRM 6006	ZRM 6013+	ZRM 6014	ZRM 6010
Measurements	RL	X	X	X
	Qd	X	X	X
Measurement Modes	Single Measurement	X	X	X
	Average of multiple measurements		X	X
	Wet timer		X	X
Data Handling	Built-in data storage		X	X
	Data transfer to PC with USB		X	X
	Data transfer to PC with Bluetooth			X
	Data management software		X	X
PRO Features	GPS		X	X
Advanced Features	Built-in printer		0	0
	Camera		0	0
	Compass		0	0
	Level meter		0	0
Handle	Short	X	X	
	Short / Long (adjustable)			X
Wheels			X	X

Zehntner ZRM


Specifications




	ZRM 6006	ZRM 6013+	ZRM 6014	ZRM 6010
Measuring	Area	WxL	52 x 218 mm	52 x 489mm
	Range	RL	0 - 4'000 mcd•m-2•lx-1	
		Qd	0 - 400 mcd•m-2•lx-1	NA
	Repeatability		± 2 %	
	Measuring time	RL/Qd	≈2 s	
		Single	≈1 s	
Optical System	Observation Angle	EN 1436 & ASTM E2302	2.29°	
	Built-in printer	ASTM E1710	1.05°	
	Equivalent observation distance		30 m, according to CEN-geometry	
	Illumination Angle RL	EN 1436	1.24°	
		ASTM E1710	88.76°	
	Illumination Angle Qd		Diffuse Illumination	
Display			Transflective luminous LCD display with LED backlight	Touchscreen 5.7" color TFT (LCD), LED backlight, VGA resolution
Data	Memory capacity		NA	1 GB internal flash memory
			NA	1'000'000 measurements
	Data Interface		NA	Host USB (type A) Host USB (type A) & Bluetooth Host USB (type A), Client Mini USB (type B)
PC Software			NA	Mapping Tools
Camera	Resolution		NA	5-megapixel 9.5x zoom
	Picture Size		NA	2592 x 1944 px
	Picture Format		NA	Jpg
Operating Temperature			-10°C to +50°C, non-condensing	0°C to +50°C, non-condensing
Material Housing			Anodized Aluminium	
Weight			6.4kg 6.8kg	7.6kg 6.4kg
Dimensions			560 x 190 x 280 mm	658.5 x 190 x 408.5 mm 340 x 152 x 575 mm

ZRM Product Lineup

Road Marking Inspection



Zehntner ZRM 6013+



Zehntner ZRM 6014



Dynamic Retroreflectometer

Vehicle-mounted retroreflectometer for safe and efficient continuous measurements



Reliability

Vehicle-mounted with 300 measurements per second guaranteeing accurate and continuous coverage for all types of colors and road markings.



Accuracy

Handheld precision at up to 150 km/h (93 mph) without obstructing traffic and for all light conditions, even in bright sunlight.



User Experience

Measurements can be evaluated with the free mapping tools software on an industrial-grade touchscreen tablet with a multilingual user interface.

Zehntner ZDR 6020 RL

Specifications

Measuring	Area	WxL	≥1000 mm x 880 mm
	Resolution		Data recording with 300 measurements per second
	Range	RL	0 - 4'000 mcd•m ⁻² •lx ⁻¹
	Profiled Markings		≈20 mm (0.79")
	Distance	In front of measuring head	6 m
	Speed	Max.	150 km/h
Optical System	Accuracy		Handheld precision at up to 150 km/h
	Observation Angle	EN 1436	2.29°
		ASTM E 1710	1.05°
	Illumination Angle RL	EN 1436	1.24°
		ASTM E1710	88.76°
	Illumination Angle Qd		Diffuse Illumination
Display			11.6 in. touchscreen tablet with installed ZDR 6020 RetroGrabber software and microphone
Weight			10.5 kg
Reporting Software	PC Software		Mapping Tools
Camera	Picture interval		10m
Temperature	Operating		0°C to 55°C, non-condensing
	Storage		-15°C to +60°C, non-condensing
Dimensions			270 x 207 x 310 mm
Special Features	Languages		German, English, Spanish, French Italian, Russian, Chinese, Korean



Zehntner ZRS 6060



Sign Retroreflectometer

Visibility measurement of traffic and road signs and reflective materials



Zehntner ZRS 6060

Bar Code Reader
Track sign identity

GPS
Allows easy data evaluation on Google Earth

Angle adaptors
Illumination angle adaptors


Robust & Professional Housing
Resistant & Stable in the field



17 Languages
Easy-to-use menu navigation

Ergonomic
Tilttable Display
Light Weight

Connectivity
Bluetooth ® & USB cables



Versatility

Superior ergonomics and screen readability, thanks to the adjustable display. Measure the night visibility of traffic signs, safety garments, conspicuity tapes, and other reflective materials.



Accuracy

A new benchmark of accuracy and robustness under any conditions in the field with optics to monitor the environment and adjust to stray light.



Productivity

Enrich your measurements with precise geolocation and high-resolution images and create comprehensive reports quickly and with ease.

Zehntner ZRS 6060



Model Selector

ZRS 6060 is available in three models (Basic, Pro & Advanced) depending on the chosen features depicted in the following Model table:



Model

Features	Basic	Pro	Advanced
RA Measurements	X	X	X
Data Transfer to PC with USB	X	X	X
Data Transfer to PC with Bluetooth	X	X	X
MappingTools PC Software	X	X	X
GPS		X	X
QR/Bar Code Reader			X
Camera			X

All three models can be selected with one of the default measurement geometries (ASTM, CEN, EN, CD, DE & ECE), with a preinstalled front mounted illumination angle adapter, as depicted in the model variant table.

If required, other illumination angle adapter variants can be purchased on the ZRS6060.

Model variant

Features	X	ASTM	CEN	EN	CD	DE	ECE*
Qd	-4°	X					
	5°		X	X	X	X	
Single Measurement	5°						X
Observation (a)	0.2°/12'	X		X	X	X	
	0.33°/20'		X	X	X	X	X
	0.5°/30'	X	X		X		
	1°	X	X			X	
	1.5°						
	2°			X			

***Note:** ECE variant is available in ZRS 6060 Basic & Advanced models.
Contact our sales representatives if a pro model is required.

Zehntner ZRS 6060

Specifications

Anodized aluminium material



Measuring	Area	25 mm
	Range	0 - 2'000 cd·lx·1·m-2
	Time	≈3 s
Memory	Type	Internal flash memory
	Size	1 GB
	Capacity	1'000'000 measurements without pictures
Interface		Host USB (type A), Client Mini USB (type B)
Touchscreen Display		3.5" color TFT (LCD), LED backlight, HVGA resolution
Camera	Resolution	5-megapixel
	Picture Size	2592 x 1944 px
		JPG
Battery		Li-Ion 14.4 V / 6.5 Ah
Operating Conditions		-10°C to +55°C
		20 to 85% rH
Storage Conditions		-20°C to +55°C
	Barcode reader	20 to 90% rH
Material Housing		Anodized aluminium
Dimensions	LxWxH	220 x 85 x 290 mm
Weight		1.9kg net without options


Accessories

		Model variant					
		ASTM	CEN	EN	CD	DE	ECE*
Optional adapters for illumination Angle (β_1)	10°	X	X	X	X	X	
	15°	X	X	X	X	X	
	20°	X	X	X	X	X	
	30°	X	X	X	X	X	X
	40°	X	X	X	X	X	
Voltage converter to be plugged into the cigarette lighter DC/AC 12V/230V		X	X	X	X	X	X
Portable USB-printer Only compatible with ZRS 6060 Advanced		X	X	X	X	X	
Handle 1.2m incl. fork		X	X	X	X	X	
Extendable handle 1.7-3m incl. fork		X	X	X	X	X	X
Extendable handle 2.2-4m incl. fork		X	X	X	X	X	X

* ECE variant is using β_2 angle

Product Lineup

Road Marking Inspection



Zehntner ZRS 6060



Zehntner ZMM 5000



Road Marking Thickness

Unique digital dry film and road markings gauge



Ease of Use

Superior ergonomics and screen readability thanks to the digital adjustable display, measuring results within seconds.



Reliability

Sturdy construction that can extract representative measurements on wide road markings with its optional measuring bridge.



Performance

Reliable measuring, including those relative to the substrate or to the marking itself (upwards and downwards measurements).

Zehntner ZMM 5000

Specifications



Material	Red Anodised Aluminium
Measuring Range	-12.5mm to/bis +12.5mm (optional)
Resolution	10µm
Bearing Area (WxL)	Min. 67 x 100 mm
Display	Digital
Dimensions (LxWxH)	180 x 70 x 80 mm
Weight	880g



Zehntner Mapping Tools



For ZRS 6060, ZRM 6014 & ZRM 6013+

The complementary MappingTools, versatile mapping and data analysis software makes administration & analysis of your measurements simple and easy. View your data, create PDF reports, export your data to XLS or to KMZ format to display your data with Google Earth™.

MappingTools is compatible with Windows® 10, Windows® 8, Windows® 7, Windows Vista® & Windows® XP SP2.



For any more information, feel free to schedule a demo.

Contact us!



<https://www.screeningeagle.com/en/contact-us>

HEADQUARTERS

Proceq AG
Ringstrasse 2
8603 Schwerzenbach
Switzerland
Headquarters: +41 43 355 38 00
Sales Europe: +41 43 588 34 92
Support Europe: +41 43 508 17 02

EMEA

Proceq AG
Ringstrasse 2
8603 Schwerzenbach
Switzerland
Sales Europe: +41 43 588 34 92
Support Europe: +41 43 508 17 02

Screening Eagle UK Limited

Bedford i-Lab,
Stannard Way, Priory Business Park
Bedford, MK44 3RZ
United Kingdom
T +44 1234 923816

Screening Eagle Spain S.L.

Calle Pepita Barrientos 7
Office 14
29004 Málaga
Spain
T +34 9517 65584

Screening Eagle Singapore Pte. Ltd.

1 Fusionopolis Way
Connexis South Tower #20-03
138632 Singapore
Singapore
T +65 6331 4151

Proceq Trading Shanghai Co. Ltd.

Room 3A, No. 315
Guangyuan West Road
Xuhui District, Shanghai
China, 2000302
T +86 21 6317 7479

AMER

Screening Eagle USA, Inc.
117 Corporation Drive
Aliquippa, PA 15001
United Arab Emirates
T +971 6 557 8505

Screening Eagle Brazil Ltda.

Rua Paes Leme 136,
Pinheiros, Sao Paulo
SP 05424-010
Brasil
T +55 11 3083 3889



ScreeningEagle.com